

NKR-AC 006 Fali kivitelű AC töltő



NKR AC 006

Lakossági felhasználásra ajánljuk elsősorban fali kivitelű egyszerűen telepíthető töltőnket, mely akár állvánnyal is rendelhető. Applikáción keresztül valós idejű felügyelettel távolról is van lehetőségünk vezérelni az eszközt. Teljesítménye 7 kW és 22 kW között használható, a rendelkezésre álló fázisoktól függően.

Product Information	Input Power Rating & Current	Single phase: Type2:7kw/32A Three phase: Type2:11kw/16A; 22kw/32A
	Output Power Rating & Current	Single phase: Type2:7kw/32A Three phase: Type2:11kw/16A; 22kw/32A
	Input Voltage&Frequency	Single phase:230VAC±10% Three phase:400VAC±10% 50 / 60 Hz
	Output Voltage&Frequency	Single phase:230VAC±10% Three phase:400VAC±10% 50 / 60 Hz
	Standby Power	<2w
	Charging outlet	Single Type2 (Socket/Cable)
	Protection	Over voltage/under voltage protection, Over current protection, PEN detection
	Special protection	Anti-UV protection
	Measuring accuracy	Class 1
User Interface	Connectivity	WIFI,Ethernet (optional) , 4G (optional)
	User Authentication	APP
	User Interface	Emergency Stop/LED indicator
	Software Update	web portal
General Characteristics	IP and IK rating	IP54
	Operating altitude	<2000m
	Operating temperature	-30° C ~ +55° C
	Working Humidity	5%~ 95%
	Cooling	Natural air cooling
	Mounting	Wall-mounted,Floor stand(Optional)
	Dimensions	H350*W196*T150mm
	Weight	3KG (without cable)
	Cable Length	≥4.8m (External line)
Shell Material	ABS	
Certification And Standards	Standard	EN/IEC 61851-1:2019 EN/IEC 61851-22:2002 EN/IEC 61000-6-3: 2007+A1:2011 EN/IEC 61000-6-1:2019